



SPECIFICATION:

- 1). Driving: Duty:1/32, Bias:1/5, V_{dd}:5.0V, V_{lcd}:4.6V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Blue
- 3). Operating temp.:0°C~+50°C
- 4). Storage temp.: -10°C~+60°C
- 5). Control IC: ST7920 (Dr Compatible)
- 6). BACKLIGHT: EDGE,WHITE
- 7). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "<" ARE REFERENCED
- 8). All the raw materials are ROHS compliant

并口接口:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	AO	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

串口接口:

17	18	19	20	21	22	23	24
VSS	VDD	VO	SCLK	SID	/CS	BLA	BLK

J2接2(VDD), 10K
J2接1(VSS), 10K
低有效

J1, 调节对比度电阻

REV	REVISION RECORD	DATE
A0	First issue	12/06



深圳市三元晶科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd

MODEL NO. 模组型号	SYB12232AZKV12	GENERAL TOL: ±0.3
APPROVED BY	CHECKED BY	PAGE: 1 OF 1
DRAWING BY		UNIT: mm
		PROJECTION 三角法