



SPECIFICATION:

- 1). Driving: Duty:1/16, Bias:1/5, Vdd:5.0V, Vlcd:3.9V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Positive/Transflective/YG
- 4). Operating temp.: 0°C~+50°C
- 5). Storage temp.: -10°C~+60°C
- 6). Control IC: SPLC780D1(Or Compatible)
- 7). BACKLIGHT: Edge,YG
- 8). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	Vo	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REVISION RECORD		REV	深圳市三元晶科技有限公司 Shenzhen TCC LCD Hi-Tech Co., Ltd													
First issue		A0														
DRAWING NO.		SYB1602EV10-5C10YL3-BSN GENERAL TOL:														
APPROVED BY		CHECKED BY	DRAWING BY		UNIT:	mm										PAGE
			YJQ			2010/9/16										1/1